



Robotic Arm

Payload		20kg
Radius		1800mm
Accuracy		±0.1mm
Axis		6
Joints rotation	J1-J6	±360°
	J1-J2	125°/s
	J3	150°/s
Joints speed	J3	150°/s
	J4-J6	210°/s
Typical TCP Speed		2.0 m/s
IP rating		IP65 (optional IP68)
Temperature range		-10~50°C
Relative humidity		<90% (non-condensing)
Noise reduction		<70db
Typical power usage		625w
Mounting		Any angle
Tool I/O connector		T1: M8, 8pin T2: Ø 12.8mm, 4pin
Tool I/O ports		4 config. DI / DO; 1 AI, 1 AO
Tool I/O power supply		T1: 0 / 12V / 24V; 3A / 2A / 1A T2: 24 V; 5A
Tool I/O communication		RS485
Footprint		Ø 240 mm
Weight		60 kg
Material		Aluminum, steel, plastic, rubber
Cable length		5.5m*
Certifications		ISO 13849, ISO 10218, ISO/TS 15066, ISO 14644 cleanroom class 5, RoHS; SEMI-S2; UL, CE, KCs
Programming		Python-script, graphical proprietary user interface, free-drag/offline programming

* Optional cable lengths of 1.5m, 3m and 10m and additional extensions up to 10m are available.



Equipped with a dual 3A/5A tool connector for enhanced power, CS620 features a 20 kg payload and the longest reach of all CS cobots, and can effectively perform palletizing, welding and other demanding tasks, and handle multiple devices simultaneously.

Standard controller

Type	AC
I/O ports	24 DI, 24 DO (8 safety config. DI/DO); 2 AI, 2 AO; 4 High-Speed DI
I/O power supply	24V/3A (internal), 6A (external)
Communication	RS485, Ethernet TCP/IP, Modbus TCP/RTU, Ethernet/IP slave, Profinet slave
Size	505 mm x 257 mm x 447 mm
IP Rating	IP44
Weight	15 kg
Power source	100~240 VAC, 50~60 Hz
Temperature range	0~50°C
Relative humidity	95% (non-condensing)
Material	Aluminum, Steel



The standard controller integrates a holder to optionally attach the TP

OEM controller

Type	DC / AC
I/O ports	24 DI, 24 DO (8 safety config. DI/DO); 2 AI, 2 AO; 4 High-Speed DI
I/O power supply	24V/3A (internal), 6A (external)
Communication	RS485, Ethernet TCP/IP, Modbus TCP/RTU, Ethernet/IP slave, Profinet slave
Size	495mm x 200mm x 227mm
IP Rating	IP40
Weight	7.5 kg
Power source	AC: 100~240 VAC, 50~60 Hz DC: 40~55VDC
Temperature range	0~50°C
Relative humidity	95% (non-condensing)
Material	Aluminum, Steel



The optional OEM controller is suitable for integrators, OEM partners and users who want to create their own custom design.

Teach Pendant

	ERP400	ERP400S
Size	301mm x 232mm x 54mm	301mm x 232mm x 105mm
Screen size	12.1"	
Resolution	1280 x 800 pixels	
IP rating	IP54	
Weight	1.7 kg	1.8 kg
Cable length	5.5 m	
Temperature range	0~50°C	
Relative humidity	5%~95% (non-condensing)	
Material	Aluminum, plastic, rubber	
Input method	Capacitive full touch-screen	Capacitive full touch-screen, 3-mode enable key, jogging-keys, function keys



The CS teach pendant contains Elite Robots proprietary software. The optional ERP400S version integrates jogging and function keys and a 3-mode enable key for enhanced safety.

